



Key Highlights:

- Type: 100G Passive Breakout Cable
- Compatibility: Multi-Vendor MSA Compatible
- Media Type: Passive Copper Cable
- Max. Distance: 3 m
- Data Rate: 48.48-100.125 Gbps
- Temperature: Standard 0°-70°C
- Low Power Consumption: 0.02W (Typical)

100G Passive Breakout Cable: 100G-PDAC-QSFP-2SFP

Product Description:

100G-PDAC-QSFP-2SFP is Multi-Vendor MSA Compatible 100G Passive Breakout Cable, operating over passive copper cable. 100G Passive breakout cable is equipped with MSA standard compatible QSFP+ transceiver assembly at one end of cable and SFP+ assembly at each end of two breakouts supporting 50G IEEE P802.3cd line rates. As passive Breakout cables do not support any electrical transmission signal boosting or regeneration, length of 100G Passive Breakout cable is limited up to 3 meters, which is enough to support 100G connections within same or neighboring equipment racks. 100G Passive Breakout cable supports 2 separate fully duplex copper data lanes, which support 48.48-100.125 Gbps multi-rate communication and such applications as 100G Ethernet (100.125Gbps) | 2 x InfiBand EDR(48.48Gbps). Most popular applications of 100G Passive Breakout Cables are cost effective close range interconnections within equipment room of telecom operators or data centers, interconnecting LAN or SAN applications with speeds up to 100G.

100G Passive Breakout Cable is CE/RoHS certified and it is Compliant with product safety standards. 100G-PDAC-QSFP-2SFP is fully compliant to QSFP28 Multi Source Agreement SFF-8665 and SFP28 Multi Source Agreement SFF-8402. Consequently, it means that module is compatible with 80% of networking equipment, where is not implemented a special algorithm for protection against third party modules. However – we can provide 100G Passive Breakout Cable with custom-encoded firmware in order to make it work almost in any equipment and we can support encoding of each end to support different vendor equipment, allowing using 100G Passive Breakout Cable as cross-platform interconnection medium. We will be glad to hear Your requirements and our sales team will check all relevant details with You during ordering procedure. Our focus is providing top quality service, we are performing serious quality checks before delivery of our products.



Product Specification:

Parameter	Value
Media Type:	Passive Breakout Cable
DAC Copper Type:	AWG30
Maximum Distance:	1m 2m 3m
Supported Data Rate:	48.48-100.125 Gbps
Supported Applications:	100G Ethernet (100.125Gbps) 2 x InfiniBand EDR(48.48Gbps)
DDM/DOM:	Supported
Connectors:	QSFP+ / SFP+
Temperature Range:	Standard 0°-70°C
Power:	+3.3V single power supply
Power Consumption:	0.02W (Typical)
MTBF value at 35 °C:	1'000'000 Hours.
Compliance:	SFF-8665 SFF-8402 QSFP28 MSA SFP28 MSA IEEE P802.3cd ROHS CE

Supported Versions:

PN	Description
100G-PDAC-QSFP-2SFP-1	Multi-Vendor Compatible 100G QSFP28 to 2xSFP+ Twinax Passive Copper Breakout Cable (48.48-100.125 Gbps, Max. 1m, AWG 30, Temp. 0-70C)
100G-PDAC-QSFP-2SFP-2	Multi-Vendor Compatible 100G QSFP28 to 2xSFP+ Twinax Passive Copper Breakout Cable (48.48-100.125 Gbps, Max. 2m, AWG 30, Temp. 0-70C)
100G-PDAC-QSFP-2SFP-3	Multi-Vendor Compatible 100G QSFP28 to 2xSFP+ Twinax Passive Copper Breakout Cable (48.48-100.125 Gbps, Max. 3m, AWG 30, Temp. 0-70C)



Compatibility:

EDGE Optical transceivers can be provided with custom-encoded firmware, in order to provide compatibility with more than 50 vendor brands in data and telecom communications industry:

MS - General MSA
AD - ADVA
AL - Alcatel-Lucent
AR - Arista
AV - Avaya
BR - Brocade
CN - Ciena
CI - Cisco
DL - Dell & Force10
DK - D-Link
EM - EMC2
ET - Enterasys

ER - Ericsson
EX - Extreme Networks
F5 - F5 Networks
FO - Fortinet
FU - Fujitsu
H3 - H3C
HI - Hirschmann
HP* - HP Networking
HS* - HP Storage
HU - Huawei
IB - IBM
IF - Infinera

IN - Intel
JU - Juniper Networks
LI - Linksys
ML - Mellanox
ME - Meraki (Cisco)
MT - MikroTik
MO - Moxa
MR - MRV
NG - Netgear
NS - NSN
PA - Palo Alto Network
QL - Qlogic

RD - RAD
RU - Ruijie Networks
SM - Supermicro
SY - Synology
TC - Telco Systems
TP - TP-LINK
TN - Trendnet
WG - WatchGuard
ZT - ZTE
XX - Other

Warranty:

EDGE Optic's provides a limited **warranty for sixty (60) months** from Purchaser's receipt of the Equipment represented in this data sheet against defective design or workmanship.

