



## PRODUCT DATA SHEET

### Optical Transceiver: 2.67G-SFP-2D

#### Description:

2.67G-SFP-2D is multi-vendor compatible SFP Transceiver module, operating over double fiber single-mode optical cable with maximum distance 2km. 2.67G-SFP-2D uses 1310nm transmitting FP laser and 1310nm PIN receiver and supports 100Mbps-2.67Gbps data rates.

2.67G-SFP-2D SFP Transceiver is fully compliant to SFP Multi Source Agreement SFF-8472 and it can be provided with custom-encoded firmware, in order to provide compatibility of most equipment vendors platforms in data communications industry.

#### Key Highlights:

- **Type:** SFP
- **Tx/Rx Wavelength:** 850/850 nm
- **Media Type:** Multi-Mode Fiber
- **Optical Budget:** 7.5-11.5 dB \*
- **Max. Distance:** 300m
- **Data Rate:** 100Mbps-2.67Gbps
- **Temperature:** Standard 0°-70°C

# TECHNICAL SPECIFICATION

Parameter	Value
<b>Product Type:</b>	2.67G-SFP-2D
<b>Media Type:</b>	Single-Mode Fiber
<b>TX Wavelength:</b>	1310 nm
<b>RX Wavelength:</b>	1310 nm
<b>Minimum Optical Budget:</b>	8.5-12.5 dB
<b>Maximum Distance:</b>	2 km
<b>Supported Data Rate:</b>	100 Mbps-2.67Gbps
<b>Supported Applications:</b>	<ul style="list-style-type: none"> <li>• STM-16 (2.488Gbps) - 7.5 dB</li> <li>• STM-4 (622Mbps) - 10.5 dB</li> <li>• STM-1 (155Mbps) - 11.5 dB</li> <li>• 100M Ethernet (100Mbps) - 11.5 dB</li> <li>• 1G Eth (1.25Gbps) - 10.5 dB</li> <li>• 1G FC (1.063Gbps) - 10.5 dB</li> <li>• 2G FC (2.125Gbps) - 8.5 dB</li> <li>• OTU1 (2.67Gbps) - 7.5 dB</li> <li>• ODU0 (1.24416Gbps) - 10.5 dB</li> <li>• ODU1 (2.499Gbps) - 7.5 dB</li> <li>• CPRI (2.458 Gbps) - 7.5 dB</li> <li>• CPRI (1.229 Gbps) - 10.5 dB</li> <li>• CPRI (614.4 Mbit/s) - 10.5 dB</li> <li>• OBSAI (1.536 Gbps) - 10.5 dB</li> <li>• OBSAI (768 Mbps) - 10.5 dB</li> </ul>
<b>DDM/DOM:</b>	Supported
<b>Temperature Range:</b>	Standard 0°-70°C
<b>Connectors:</b>	Double LC
<b>Tx Wavelength Bandwidth:</b>	100 nm (1260-1360 nm)
<b>Rx Wavelength Bandwidth:</b>	100 nm (1260-1360 nm)
<b>Transmitting Power (Min/Max):</b>	-9.5/-3 dB
<b>Receiver Sensitivity:</b>	-18 / -21 dB Based on Data Rate
<b>Receiver Overload:</b>	-3 dB
<b>Dispersion:</b>	100-110 ps/nm
<b>Laser:</b>	FP
<b>Receiver Type:</b>	PIN
<b>Chip:</b>	SEMTECH/UX

Parameter	Value
<b>Power:</b>	+3.3V single power supply
<b>Compliance:</b>	<ul style="list-style-type: none"> <li>• SFP MSA,</li> <li>• SFF-8472,</li> <li>• RoHS, CE,</li> <li>• Class 1 FDA</li> <li>• IEC60825-1 Laser Safety Compliant</li> </ul>

## Compatibility

EDGE Optical transceivers can be provided with custom-encoded firmware, in order to provide compatibility with more than 50 vendor brands in data and telecom communications industry:

**MS** - General MSA  
**AD** - ADVA  
**AL** - Alcatel-Lucent  
**AR** - Arista  
**AV** - Avaya  
**BR** - Brocade  
**CN** - Ciena  
**CI** - Cisco  
**DL** - Dell & Force10  
**DK** - D-Link  
**EM** - EMC2  
**ET** - Enterasys

**ER** - Ericsson  
**EX** - Extreme Networks  
**F5** - F5 Networks  
**FO** - Fortinet  
**FU** - Fujitsu  
**H3** - H3C  
**HI** - Hirschmann  
**HP\*** - HP Networking  
**HS\*** - HP Storage  
**HU** - Huawei  
**IB** - IBM  
**IF** - Infinera

**IN** - Intel  
**JU** - Juniper Networks  
**LI** - Linksys  
**ML** - Mellanox  
**ME** - Meraki (Cisco)  
**MT** - MikroTik  
**MO** - Moxa  
**MR** - MRV  
**NG** - Netgear  
**NS** - NSN  
**PA** - Palo Alto Network  
**QL** - Qlogic

**RD** - RAD  
**RU** - Ruijie Networks  
**SM** - Supermicro  
**SY** - Synology  
**TC** - Telco Systems  
**TP** - TP-LINK  
**TN** - Trendnet  
**WG** - WatchGuard  
**ZT** - ZTE  
**XX** - Other

\* - Please note HP compatible module prices can be higher than prices indicated in this material due to special requirements in coding. If you require HP compatibility, for exact pricing please contact our sales team: [sales@edgeoptic.com](mailto:sales@edgeoptic.com)

## Product Quality

We focus on strict product quality tests before each delivery, performing optical parameter tests, connector cleanliness tests and firmware verification tests to ensure our delivered products fully meets the promised product technical specification and compatibility requirements.

EDGE Optical transceivers are CE, ROHS certified and have passed Telecordia reliability tests.

## Warranty

EDGE Optic's provides a limited **warranty for sixty (60) months** from Purchaser's receipt of the Equipment represented in this data sheet against defective design or workmanship.