



PRODUCT DATA SHEET

Optical Transceiver: 2.67G-SFP-300D

Description:

2.67G-SFP-300D is multi-vendor compatible SFP Transceiver module, operating over double fiber multi-mode optical cable with maximum distance 300m. 2.67G-SFP-300D uses 850nm transmitting VSCSEL laser and 850nm PIN receiver and supports 100Mbps-2.67Gbps data rates.

2.67G-SFP-300D SFP Transceiver is fully compliant to SFP Multi Source Agreement SFF-8472 and it can be provided with custom-encoded firmware, in order to provide compatibility of most equipment vendors platforms in data communications industry.

Key Highlights:

- **Type:** SFP
- **Tx/Rx Wavelength:** 850/850 nm
- **Media Type:** Multi-Mode Fiber
- **Optical Budget:** 7.5-11.5 dB *
- **Max. Distance:** 300m
- **Data Rate:** 100Mbps-2.67Gbps
- **Temperature:** Standard 0°-70°C

TECHNICAL SPECIFICATION

Parameter	Value
Product Type:	2.67G-SFP-300D
Media Type:	Multi-Mode Fiber
TX Wavelength:	850 nm
RX Wavelength:	1550 nm
Minimum Optical Budget:	850 nm
Maximum Distance:	300 m
Supported Data Rate:	100 Mbps-2.67Gbps
Supported Applications:	<ul style="list-style-type: none"> • STM-16 (2.488Gbps) - 7.5 dB • STM-4 (622Mbps) - 10.5 dB • STM-1 (155Mbps) - 11.5 dB • 100M Ethernet (100Mbps) - 11.5 dB • 1G Eth (1.25Gbps) - 10.5 dB • 1G FC (1.063Gbps) - 10.5 dB • 2G FC (2.125Gbps) - 8.5 dB • OTU1 (2.67Gbps) - 7.5 dB • ODU0 (1.24416Gbps) - 10.5 dB • ODU1 (2.499Gbps) - 7.5 dB • CPRI (2.458 Gbps) - 7.5 dB • CPRI (1.229 Gbps) - 10.5 dB • CPRI (614.4 Mbit/s) - 10.5 dB • OBSAI (1.536 Gbps) - 10.5 dB • OBSAI (768 Mbps) - 10.5 dB
DDM/DOM:	Supported
Temperature Range:	Standard 0°-70°C
Connectors:	Double LC
Tx Wavelength Bandwidth:	20 nm (840-860 nm)
Rx Wavelength Bandwidth:	20 nm (840-860 nm)
Transmitting Power (Min/Max):	-9.5/-3 dB
Receiver Sensitivity:	-17 / -21 dB Based on Data Rate
Receiver Overload:	-3 dB
Dispersion:	110 ps/nm
Laser:	VSCEL
Receiver Type:	PIN
Chip:	SEMTECH/MAXIM/UX

Parameter	Value
Power:	+3.3V single power supply
Compliance:	<ul style="list-style-type: none"> • SFP MSA, • SFF-8472, • RoHS, CE, • Class 1 FDA • IEC60825-1 Laser Safety Compliant

Compatibility

EDGE Optical transceivers can be provided with custom-encoded firmware, in order to provide compatibility with more than 50 vendor brands in data and telecom communications industry:

MS - General MSA
AD - ADVA
AL - Alcatel-Lucent
AR - Arista
AV - Avaya
BR - Brocade
CN - Ciena
CI - Cisco
DL - Dell & Force10
DK - D-Link
EM - EMC2
ET - Enterasys

ER - Ericsson
EX - Extreme Networks
F5 - F5 Networks
FO - Fortinet
FU - Fujitsu
H3 - H3C
HI - Hirschmann
HP* - HP Networking
HS* - HP Storage
HU - Huawei
IB - IBM
IF - Infinera

IN - Intel
JU - Juniper Networks
LI - Linksys
ML - Mellanox
ME - Meraki (Cisco)
MT - MikroTik
MO - Moxa
MR - MRV
NG - Netgear
NS - NSN
PA - Palo Alto Network
QL - Qlogic

RD - RAD
RU - Ruijie Networks
SM - Supermicro
SY - Synology
TC - Telco Systems
TP - TP-LINK
TN - Trendnet
WG - WatchGuard
ZT - ZTE
XX - Other

* - Please note HP compatible module prices can be higher than prices indicated in this material due to special requirements in coding. If you require HP compatibility, for exact pricing please contact our sales team: sales@edgeoptic.com

Product Quality

We focus on strict product quality tests before each delivery, performing optical parameter tests, connector cleanliness tests and firmware verification tests to ensure our delivered products fully meets the promised product technical specification and compatibility requirements.

EDGE Optical transceivers are CE, ROHS certified and have passed Telecordia reliability tests.

Warranty

EDGE Optic's provides a limited **warranty for sixty (60) months** from Purchaser's receipt of the Equipment represented in this data sheet against defective design or workmanship.