


Key Highlights:

- Type: 25G Passive Twinax Cable
- Compatibility: Multi-Vendor MSA Compatible
- Media Type: Passive Copper Cable
- Max. Distance: 5 m
- Data Rate: 10.31-28.05 Gbps
- Temperature: Standard 0°-70°C
- Low Power Consumption: 0.2W (Typical)



25G Passive Twinax Cable: 25G-PDAC-SFP28

Product Description:

25G-PDAC-SFP28 is Multi-Vendor MSA Compatible 25G Passive Twinax Cable, operating over copper cable. 25G Passive twinax cable is equipped with MSA standard compatible SFP28 transceiver assembly at each end of cable. Main difference distinguishing Passive from Active Twinax cables is that Passive cables do not support any electrical transmission signal boosting or regeneration. 25G Passive Twinax cable support 10.31-28.05 Gbps multi-rate communication and such applications as 25G Ethernet (25Gbps) | 10G Ethernet (10.31Gbps) | 32G Fiber Channel (28.05Gbps). Most popular applications of 25G Passive Twinax Cables are cost effective close range interconnections within equipment room of telecom operators or data centers, interconnecting LAN or SAN applications with speeds up to 28G.

25G Passive Twinax Cable is CE/RoHS certified and it is Compliant with product safety standards. 25G-PDAC-SFP28 is fully compliant to SFP28 Multi Source Agreement SFF-8402. Consequently, it means that module is compatible with 80% of networking equipment, where is not implemented a special algorithm for protection against third party modules. However – we can provide 25G Passive Twinax Cable with custom-encoded firmware in order to make it work almost in any equipment and we can support encoding of each end to support different vendor equipment, allowing using Passive Twinax Cable as cross-platform interconnection medium. We will be glad to hear Your requirements and our sales team will check all relevant details with You during ordering procedure. Our focus is providing top quality service, we are performing serious quality checks before delivery of our products



Product Specification:

Parameter	Value
Media Type:	Passive Twinax Cable
DAC Copper Type:	1m-2m AWG30 / 3-5m AWG26
Maximum Distance:	1m 2m 3m 5m
Supported Data Rate:	10.31-28.05 Gbps
Supported Applications:	25G Ethernet (25Gbps) 10G Ethernet (10.31Gbps) 32G Fiber Channel(28.05Gbps)
DDM/DOM:	Supported
Connectors:	SFP+
Temperature Range:	Standard 0°-70°C
Power:	+3.3V single power supply
Power Consumption:	0.2W (Typical)
MTBF value at 35 °C:	1'000'000 Hours.
Compliance:	SFP28 MSA SFF-8432 ROHS CE SFF-8402

Supported Versions:

PN	Description
25G-PDAC-SFP28-1	Multi-Vendor Compatible 25G SFP28 to SFP28 Twinax Passive Copper Cable (10.31-28.05 Gbps, Max. 1m, AWG 30, Temp. 0-70C)
25G-PDAC-SFP28-2	Multi-Vendor Compatible 25G SFP28 to SFP28 Twinax Passive Copper Cable (10.31-28.05 Gbps, Max. 2m, AWG 30, Temp. 0-70C)
25G-PDAC-SFP28-3	Multi-Vendor Compatible 25G SFP28 to SFP28 Twinax Passive Copper Cable (10.31-28.05 Gbps, Max. 3m, AWG 26, Temp. 0-70C)
25G-PDAC-SFP28-5	Multi-Vendor Compatible 25G SFP28 to SFP28 Twinax Passive Copper Cable (10.31-28.05 Gbps, Max. 5m, AWG 26, Temp. 0-70C)



Compatibility:

EDGE Optical transceivers can be provided with custom-encoded firmware, in order to provide compatibility with more than 50 vendor brands in data and telecom communications industry:

MS - General MSA
AD - ADVA
AL - Alcatel-Lucent
AR - Arista
AV - Avaya
BR - Brocade
CN - Ciena
CI - Cisco
DL - Dell & Force10
DK - D-Link
EM - EMC2
ET - Enterasys

ER - Ericsson
EX - Extreme Networks
F5 - F5 Networks
FO - Fortinet
FU - Fujitsu
H3 - H3C
HI - Hirschmann
HP* - HP Networking
HS* - HP Storage
HU - Huawei
IB - IBM
IF - Infinera

IN - Intel
JU - Juniper Networks
LI - Linksys
ML - Mellanox
ME - Meraki (Cisco)
MT - MikroTik
MO - Moxa
MR - MRV
NG - Netgear
NS - NSN
PA - Palo Alto Network
QL - Qlogic

RD - RAD
RU - Ruijie Networks
SM - Supermicro
SY - Synology
TC - Telco Systems
TP - TP-LINK
TN - Trendnet
WG - WatchGuard
ZT - ZTE
XX - Other

Warranty:

EDGE Optic's provides a limited **warranty for sixty (60) months** from Purchaser's receipt of the Equipment represented in this data sheet against defective design or workmanship.

