



## PRODUCT DATA SHEET

# Optical Transceiver: BIDI-1.25G-SFP-121-BDS

### Description:

BIDI-1.25G-SFP-121-BDS is multi-vendor compatible SFP Transceiver module, operating over single fiber single-mode optical cable with maximum distance 120km. BIDI-1.25G-SFP-121-BDS uses 1570nm transmitting DFB laser and 1510nm APD receiver and supports 1.063-1.25Gbps data rates. BIDI-1.25G-SFP-121-BDS SFP Transceiver is fully compliant to SFP Multi Source Agreement SFF-8472 and it can be provided with custom-encoded firmware, in order to provide compatibility of most equipment vendors platforms in data communications industry.

### Key Highlights:

- **Type:** SFP
- **Tx/Rx Wavelength:** 1570/1510 nm
- **Media Type:** Single-Mode Fiber
- **Optical Budget:** 31 dB
- **Max. Distance:** 120 km
- **Data Rate:** 1.063-1.25Gbps
- **Temperature:** Standard 0°-70°C

# TECHNICAL SPECIFICATION

Parameter	Value
<b>Product Type:</b>	BIDI-1.25G-SFP-121-BDS
<b>Media Type:</b>	Single-Mode Fiber
<b>TX Wavelength:</b>	1570 nm
<b>RX Wavelength:</b>	1510 nm
<b>Minimum Optical Budget:</b>	31 dB
<b>Maximum Distance:</b>	120 km
<b>Supported Data Rate:</b>	1.063-1.25Gbps
<b>Supported Applications:</b>	<ul style="list-style-type: none"><li>• 1G Eth (1.25Gbps)</li><li>• 1G FC (1.063Gbps)</li></ul>
<b>DDM/DOM:</b>	Supported
<b>Temperature Range:</b>	Standard 0°-70°C
<b>Connectors:</b>	Single LC
<b>Tx Wavelength Bandwidth:</b>	40 nm (1550-1590 nm)
<b>Rx Wavelength Bandwidth:</b>	40 nm (1490-1530 nm)
<b>Transmitting Power (Min/Max):</b>	0/5 dB
<b>Receiver Sensitivity:</b>	-31 dB
<b>Receiver Overload:</b>	-7 dB
<b>Dispersion:</b>	2600-2700 ps/nm
<b>Laser:</b>	DFB
<b>Receiver Type:</b>	APD
<b>Chip:</b>	SEMTECH/MAXIM/UX
<b>Power:</b>	+3.3V single power supply
<b>Compliance:</b>	<ul style="list-style-type: none"><li>• SFP MSA,</li><li>• SFF-8472,</li><li>• RoHS, CE,</li><li>• Class 1 FDA</li><li>• IEC60825-1 Laser Safety Compliant</li></ul>

## Compatibility

EDGE Optical transceivers can be provided with custom-encoded firmware, in order to provide compatibility with more than 50 vendor brands in data and telecom communications industry:

**MS** - General MSA  
**AD** - ADVA  
**AL** - Alcatel-Lucent  
**AR** - Arista  
**AV** - Avaya  
**BR** - Brocade  
**CN** - Ciena  
**CI** - Cisco  
**DL** - Dell & Force10  
**DK** - D-Link  
**EM** - EMC2  
**ET** - Enterasys

**ER** - Ericsson  
**EX** - Extreme Networks  
**F5** - F5 Networks  
**FO** - Fortinet  
**FU** - Fujitsu  
**H3** - H3C  
**HI** - Hirschmann  
**HP\*** - HP Networking  
**HS\*** - HP Storage  
**HU** - Huawei  
**IB** - IBM  
**IF** - Infinera

**IN** - Intel  
**JU** - Juniper Networks  
**LI** - Linksys  
**ML** - Mellanox  
**ME** - Meraki (Cisco)  
**MT** - MikroTik  
**MO** - Moxa  
**MR** - MRV  
**NG** - Netgear  
**NS** - NSN  
**PA** - Palo Alto Network  
**QL** - Qlogic

**RD** - RAD  
**RU** - Ruijie Networks  
**SM** - Supermicro  
**SY** - Synology  
**TC** - Telco Systems  
**TP** - TP-LINK  
**TN** - Trendnet  
**WG** - WatchGuard  
**ZT** - ZTE  
**XX** - Other

\* - Please note HP compatible module prices can be higher than prices indicated in this material due to special requirements in coding. If you require HP compatibility, for exact pricing please contact our sales team: [sales@edgeoptic.com](mailto:sales@edgeoptic.com)

## Product Quality

We focus on strict product quality tests before each delivery, performing optical parameter tests, connector cleanliness tests and firmware verification tests to ensure our delivered products fully meet the promised product technical specification and compatibility requirements.

EDGE Optical transceivers are CE, ROHS certified and have passed Telecordia reliability tests.

## Warranty

EDGE Optic's provides a limited **warranty for sixty (60) months** from Purchaser's receipt of the Equipment represented in this data sheet against defective design or workmanship.