



PRODUCT DATA SHEET

Optical Transceiver: BiDi-10G-XFP-60B

Description:

BiDi-10G-XFP-60B is multi-vendor compatible XFP Transceiver module, operating over one single-mode optical cable fiber with maximum distance 60km. BiDi-10G-XFP-60B uses 1330nm transmitting DFB laser and 1270nm PIN receiver and supports 1.24-11.3Gbps data rates.

BiDi-10G-XFP-60B XFP Transceiver is fully compliant to XFP Multi Source Agreement INF-8077i and it can be provided with custom-encoded firmware, in order to provide compatibility of most equipment vendors platforms in data communications industry.

Key Highlights:

- **Type:** XFP
- **Tx/Rx Wavelength:** 1330/1270 nm
- **Media Type:** Single-Mode Fiber
- **Optical Budget:** 20 dB
- **Max. Distance:** 60km
- **Data Rate:** 1.24-11.3Gbps
- **Temperature:** Standard 0°-70°C

TECHNICAL SPECIFICATION

Parameter	Value
Product Type:	BIDI-10G-XFP-60B
Media Type:	Single-Mode Fiber
TX Wavelength:	1330 nm
RX Wavelength:	1270 nm
Minimum Optical Budget:	20.0 dB
Maximum Distance:	60 km
Supported Data Rate:	1.24-11.3Gbps
Supported Applications:	<ul style="list-style-type: none">• 10G Eth (10.31Gbps)• 1G Eth (1.25Gbps)• STM-64 (9.95Gbps)• STM-16 (2.488 Gbps)• OTU1 (2.66Gbps)• OTU2 (10.70Gbps)• OTU1e (11.049Gbps)• OTU2e (11.095Gbps)• OTU1f (11.27Gbps)• OTU2f (11.32Gbps)• ODU0 (1.244Gbps)• ODU1 (2.498Gbps)• ODU2 (10.037Gbps)• ODU2e (10.399Gbps)• 10G FC (10.52 Gbps)• 8.5G FC (8.5 Gbps)• 4G FC (4.25 Gbps)• 2G FC (2.125 Gbps)• 1G FC (1.0625 Gbps)
DDM/DOM:	Supported
Temperature Range:	Standard 0°-70°C
Connectors:	Double LC
Tx Wavelength Bandwidth:	40 nm (1310-1350 nm)
Rx Wavelength Bandwidth:	40 nm (1250-1290 nm)
Transmitting Power (Min/Max):	0/4 dB
Receiver Sensitivity:	-20 dB
Receiver Overload:	-6 dB

Parameter	Value
Dispersion:	400-800 ps/nm
Laser:	DFB
Receiver Type:	PIN
Chip:	SEMTECH/MAXIM/MINDSPEED
Power:	+3.3V single power supply
Compliance:	XFP MSA, RoHS, CE, Class 1 FDA and IEC60825-1 Laser Safety Compliant

Compatibility

EDGE Optical transceivers can be provided with custom-encoded firmware, in order to provide compatibility with more than 50 vendor brands in data and telecom communications industry:

MS - General MSA
AD - ADVA
AL - Alcatel-Lucent
AR - Arista
AV - Avaya
BR - Brocade
CN - Ciena
CI - Cisco
DL - Dell & Force10
DK - D-Link
EM - EMC2
ET - Enterasys

ER - Ericsson
EX - Extreme Networks
F5 - F5 Networks
FO - Fortinet
FU - Fujitsu
H3 - H3C
HI - Hirschmann
HP* - HP Networking
HS* - HP Storage
HU - Huawei
IB - IBM
IF - Infinera

IN - Intel
JU - Juniper Networks
LI - Linksys
ML - Mellanox
ME - Meraki (Cisco)
MT - MikroTik
MO - Moxa
MR - MRV
NG - Netgear
NS - NSN
PA - Palo Alto Network
QL - Qlogic

RD - RAD
RU - Ruijie Networks
SM - Supermicro
SY - Synology
TC - Telco Systems
TP - TP-LINK
TN - Trendnet
WG - WatchGuard
ZT - ZTE
XX - Other

* - Please note HP compatible module prices can be higher than prices indicated in this material due to special requirements in coding. If you require HP compatibility, for exact pricing please contact our sales team: sales@edgeoptic.com

Product Quality

We focus on strict product quality tests before each delivery, performing optical parameter tests, connector cleanliness tests and firmware verification tests to ensure our delivered products fully meet the promised product technical specification and compatibility requirements.

EDGE Optical transceivers are CE, ROHS certified and have passed Telecordia reliability tests.

Warranty

EDGE Optic's provides a limited **warranty for sixty (60) months** from Purchaser's receipt of the Equipment represented in this data sheet against defective design or workmanship.