



## PRODUCT DATA SHEET

# Optical Transceiver: BIDI-2.67G-SFP-40-ADS

### Description:

BIDI-2.67G-SFP-40-ADS is multi-vendor compatible SFP Transceiver module, operating over single fiber single-mode optical cable with maximum distance 40km. BIDI-2.67G-SFP-40-ADS uses 1310nm transmitting DFB laser and 1550nm PIN receiver and supports 100Mbps-2.67Gbps data rates.

BIDI-2.67G-SFP-40-ADS SFP Transceiver is fully compliant to SFP Multi Source Agreement SFF-8472 and it can be provided with custom-encoded firmware, in order to provide compatibility of most equipment vendors platforms in data communications industry.

### Key Highlights:

- Type: SFP
- Tx/Rx Wavelength: 1310/1550 nm
- Media Type: Single-Mode Fiber
- Optical Budget: 18 - 22 dB \*
- Max. Distance: 40 km
- Data Rate: 100Mbps-2.67Gbps
- Temperature: Standard 0°-70°C

\* Depending on used application/data rate

# TECHNICAL SPECIFICATION

Parameter	Value
<b>Product Type:</b>	BIDI-2.67G-SFP-40-ADS
<b>Media Type:</b>	Single-Mode Fiber
<b>TX Wavelength:</b>	1310 nm
<b>RX Wavelength:</b>	1550 nm
<b>Maximum Distance:</b>	40 km
<b>Supported Data Rate:</b>	100 Mbps-2.67Gbps
<b>Supported Applications:</b>	<ul style="list-style-type: none"> <li>• STM-16 (2.488Gbps) - 13 dB</li> <li>• STM-4 (622Mbps) - 16 dB</li> <li>• STM-1 (155Mbps) - 16 dB</li> <li>• 100M Ethernet (100Mbps) - 16 dB</li> <li>• 1G Eth (1.25Gbps) - 16 dB</li> <li>• 1G FC (1.063Gbps) - 16 dB</li> <li>• 2G FC (2.125Gbps) - 14 dB</li> <li>• OTU1 (2.67Gbps) - 13 dB</li> <li>• ODU0 (1.24416Gbps) - 16 dB</li> <li>• ODU1 (2.499Gbps) - 13 dB</li> <li>• CPRI (2.458 Gbps) - 16 dB</li> <li>• CPRI (1.229 Gbps) - 16 dB</li> <li>• CPRI (614.4 Mbit/s) - 16 dB</li> <li>• OBSAI (1.536 Gbps) - 16 dB</li> <li>• OBSAI (768 Mbps) - 16 dB</li> </ul>
<b>DDM/DOM:</b>	Supported
<b>Temperature Range:</b>	Standard 0°-70°C
<b>Connectors:</b>	Single LC
<b>Tx Wavelength Bandwidth:</b>	40 nm (1290-1330 nm)
<b>Rx Wavelength Bandwidth:</b>	40 nm (1530-1570 nm)
<b>Transmitting Power (Min/Max):</b>	-2/3 dB
<b>Receiver Sensitivity:</b>	-20 / -24 dB Based on Data Rate
<b>Receiver Overload:</b>	-3 dB
<b>Dispersion:</b>	800-1000 ps/nm
<b>Laser:</b>	DFB
<b>Receiver Type:</b>	PIN

Parameter	Value
<b>Chip:</b>	SEMTECH/UX
<b>Power:</b>	+3.3V single power supply
<b>Compliance:</b>	<ul style="list-style-type: none"> <li>• SFP MSA,</li> <li>• SFF-8472,</li> <li>• RoHS,</li> <li>• CE,</li> <li>• Class 1 FDA and IEC60825-1 Laser Safety Compliant</li> </ul>

## Compatibility

EDGE Optical transceivers can be provided with custom-encoded firmware, in order to provide compatibility with more than 50 vendor brands in data and telecom communications industry:

**MS** - General MSA  
**AD** - ADVA  
**AL** - Alcatel-Lucent  
**AR** - Arista  
**AV** - Avaya  
**BR** - Brocade  
**CN** - Ciena  
**CI** - Cisco  
**DL** - Dell & Force10  
**DK** - D-Link  
**EM** - EMC2  
**ET** - Enterasys

**ER** - Ericsson  
**EX** - Extreme Networks  
**F5** - F5 Networks  
**FO** - Fortinet  
**FU** - Fujitsu  
**H3** - H3C  
**HI** - Hirschmann  
**HP\*** - HP Networking  
**HS\*** - HP Storage  
**HU** - Huawei  
**IB** - IBM  
**IF** - Infinera

**IN** - Intel  
**JU** - Juniper Networks  
**LI** - Linksys  
**ML** - Mellanox  
**ME** - Meraki (Cisco)  
**MT** - MikroTik  
**MO** - Moxa  
**MR** - MRV  
**NG** - Netgear  
**NS** - NSN  
**PA** - Palo Alto Network  
**QL** - Qlogic

**RD** - RAD  
**RU** - Ruijie Networks  
**SM** - Supermicro  
**SY** - Synology  
**TC** - Telco Systems  
**TP** - TP-LINK  
**TN** - Trendnet  
**WG** - WatchGuard  
**ZT** - ZTE  
**XX** - Other

\* - Please note HP compatible module prices can be higher than prices indicated in this material due to special requirements in coding. If you require HP compatibility, for exact pricing please contact our sales team: [sales@edgeoptic.com](mailto:sales@edgeoptic.com)

## Product Quality

We focus on strict product quality tests before each delivery, performing optical parameter tests, connector cleanliness tests and firmware verification tests to ensure our delivered products fully meets the promised product technical specification and compatibility requirements.

EDGE Optical transceivers are CE, ROHS certified and have passed Telecordia reliability tests.

## Warranty

EDGE Optic's provides a limited **warranty for sixty (60) months** from Purchaser's receipt of the Equipment represented in this data sheet against defective design or workmanship.