




## PRODUCT DATA SHEET

# Optical Transceiver: CWDM-10G-XENPAK-40-51

### Description:

CWDM-10G-XENPAK-40-51 is multi-vendor compatible XENPAK Transceiver module, operating over double fiber single-mode optical cable with maximum distance 40km. CWDM-10G-XENPAK-40-51 uses 1510nm transmitting DFB laser and PIN receiver supporting all ITU-T G.694.2 grid 1270-1610nm and supports 10.3125 Gbps Ethernet.

CWDM-10G-XENPAK-40-51 Transceiver is fully compliant to XENPAK MSA Rev.3 and it can be provided with custom-encoded firmware, in order to provide compatibility of most equipment vendors platforms in data communications industry.

### Key Highlights:

- **Type:** XENPAK
- **Tx/Rx Wavelength:** 1510/G.694.2 CWDM Grid (1270-1610nm)
- **Media Type:** Single-Mode Fiber
- **Optical Budget:** 14 dB
- **Max. Distance:** 40 km
- **Data Rate:** 10.3125Gbps
- **Temperature:** Standard 0°-70°C

# TECHNICAL SPECIFICATION

| Parameter                            | Value                                                                                                                                         |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product Type:</b>                 | CWDM-10G-XENPAK-40-51                                                                                                                         |
| <b>Media Type:</b>                   | Single-Mode Fiber                                                                                                                             |
| <b>TX Wavelength:</b>                | 1510 nm                                                                                                                                       |
| <b>RX Wavelength:</b>                | 1270-1610 nm                                                                                                                                  |
| <b>Minimum Optical Budget:</b>       | 14 dB                                                                                                                                         |
| <b>Maximum Distance:</b>             | 40 km                                                                                                                                         |
| <b>Supported Data Rate:</b>          | 10.3125Gbps                                                                                                                                   |
| <b>Supported Applications:</b>       | 10G Ethernet (10.3125 Gbps)                                                                                                                   |
| <b>DDM/DOM:</b>                      | Supported                                                                                                                                     |
| <b>Temperature Range:</b>            | Standard 0°-70°C                                                                                                                              |
| <b>Connectors:</b>                   | Double LC                                                                                                                                     |
| <b>Tx Wavelength Bandwidth:</b>      | 20 nm (1500nm-1520nm)                                                                                                                         |
| <b>Rx Wavelength Bandwidth:</b>      | G.694.2 grid: 1270-1610 nm                                                                                                                    |
| <b>Transmitting Power (Min/Max):</b> | -2 / 3 dB                                                                                                                                     |
| <b>Receiver Sensitivity:</b>         | -16 dB                                                                                                                                        |
| <b>Receiver Overload:</b>            | -3 dB                                                                                                                                         |
| <b>Dispersion:</b>                   | 800-1000 ps/nm                                                                                                                                |
| <b>Laser:</b>                        | DFB                                                                                                                                           |
| <b>Receiver Type:</b>                | PIN                                                                                                                                           |
| <b>Chip:</b>                         | SEMTECH/MAXIM/MINDSPEED                                                                                                                       |
| <b>Power:</b>                        | +3.3V single power supply                                                                                                                     |
| <b>Compliance:</b>                   | <ul style="list-style-type: none"> <li>• XENPAK MSA Rev.3,</li> <li>• CE, Class 1 FDA</li> <li>• IEC60825-1 Laser Safety Compliant</li> </ul> |

## Compatibility

EDGE Optical transceivers can be provided with custom-encoded firmware, in order to provide compatibility with more than 50 vendor brands in data and telecom communications industry:

**MS** - General MSA  
**AD** - ADVA  
**AL** - Alcatel-Lucent  
**AR** - Arista  
**AV** - Avaya  
**BR** - Brocade  
**CN** - Ciena  
**CI** - Cisco  
**DL** - Dell & Force10  
**DK** - D-Link  
**EM** - EMC2  
**ET** - Enterasys

**ER** - Ericsson  
**EX** - Extreme Networks  
**F5** - F5 Networks  
**FO** - Fortinet  
**FU** - Fujitsu  
**H3** - H3C  
**HI** - Hirschmann  
**HP\*** - HP Networking  
**HS\*** - HP Storage  
**HU** - Huawei  
**IB** - IBM  
**IF** - Infinera

**IN** - Intel  
**JU** - Juniper Networks  
**LI** - Linksys  
**ML** - Mellanox  
**ME** - Meraki (Cisco)  
**MT** - MikroTik  
**MO** - Moxa  
**MR** - MRV  
**NG** - Netgear  
**NS** - NSN  
**PA** - Palo Alto Network  
**QL** - Qlogic

**RD** - RAD  
**RU** - Ruijie Networks  
**SM** - Supermicro  
**SY** - Synology  
**TC** - Telco Systems  
**TP** - TP-LINK  
**TN** - Trendnet  
**WG** - WatchGuard  
**ZT** - ZTE  
**XX** - Other

\* - Please note HP compatible module prices can be higher than prices indicated in this material due to special requirements in coding. If you require HP compatibility, for exact pricing please contact our sales team: [sales@edgeoptic.com](mailto:sales@edgeoptic.com)

## Product Quality

We focus on strict product quality tests before each delivery, performing optical parameter tests, connector cleanliness tests and firmware verification tests to ensure our delivered products fully meets the promised product technical specification and compatibility requirements.

EDGE Optical transceivers are CE, ROHS certified and have passed Telecordia reliability tests.

## Warranty

EDGE Optic's provides a limited **warranty for sixty (60) months** from Purchaser's receipt of the Equipment represented in this data sheet against defective design or workmanship.