



## PRODUCT DATA SHEET

# Optical Transceiver: CWDM-2.67G-SFP-120-51

### Description:

CWDM-2.67G-SFP-120-51 is multi-vendor compatible SFP Transceiver module, operating over double fiber single-mode optical cable with maximum distance 120km. CWDM-2.67G-SFP-120-51 uses 1510nm transmitting DFB laser and APD receiver supporting all ITU-T G.694.2 grid 1270-1610nm and supports 100Mbps-2.67Gbps data rates. CWDM-2.67G-SFP-120-51 SFP Transceiver is fully compliant to SFP Multi Source Agreement SFF-8472 and it can be provided with custom-encoded firmware, in order to provide compatibility of most equipment vendors platforms in data communications industry.

### Key Highlights:

- Type: SFP
- Tx/Rx Wavelength: 1510nm/G.694.2 CWDM Grid (1270-1610nm)
- Media Type: Single-Mode Fiber
- Optical Budget: 30-34 dB \*
- Max. Distance: 120km
- Data Rate: 100Mbps-2.67Gbps
- Temperature: Standard 0°-70°C

\* Depending on used application/data rate

# TECHNICAL SPECIFICATION

Parameter	Value
<b>Product Type:</b>	CWDM-2.67G-SFP-120-51
<b>Media Type:</b>	Single-Mode Fiber
<b>TX Wavelength:</b>	1510 nm
<b>RX Wavelength:</b>	1270-1610 nm
<b>Maximum Distance:</b>	120 km
<b>Supported Data Rate:</b>	100 Mbps-2.67Gbps
<b>Supported Applications:</b>	<ul style="list-style-type: none"> <li>• STM-16 (2.488Gbps) - 15 dB</li> <li>• STM-4 (622Mbps) - 18 dB</li> <li>• STM-1 (155Mbps) - 19 dB</li> <li>• 100M Ethernet (100Mbps) - 19 dB</li> <li>• 1G Eth (1.25Gbps) - 18 dB</li> <li>• 1G FC (1.063Gbps) - 18 dB</li> <li>• 2G FC (2.125Gbps) - 16 dB</li> <li>• OTU1 (2.67Gbps) - 15 dB</li> <li>• ODU0 (1.24416Gbps) - 18 dB</li> <li>• ODU1 (2.499Gbps) - 15 dB</li> <li>• CPRI (2.458 Gbps) - 15 dB</li> <li>• CPRI (1.229 Gbps) - 18 dB</li> <li>• CPRI (614.4 Mbit/s) - 18 dB</li> <li>• OBSAI (1.536 Gbps) - 18 dB</li> <li>• OBSAI (768 Mbps) - 18 dB</li> </ul>
<b>DDM/DOM:</b>	Supported
<b>Temperature Range:</b>	Standard 0°-70°C
<b>Connectors:</b>	Double LC
<b>Tx Wavelength Bandwidth:</b>	20 nm (1500nm-1520nm)
<b>Rx Wavelength Bandwidth:</b>	G.694.2 grid: 1270-1610 nm
<b>Transmitting Power (Min/Max):</b>	0/5 dB
<b>Receiver Sensitivity:</b>	-30/-34 dB Based on Data Rate
<b>Receiver Overload:</b>	-7 dB
<b>Dispersion:</b>	2600-2700 ps/nm
<b>Laser:</b>	DFB
<b>Receiver Type:</b>	APD

Parameter	Value
<b>Chip:</b>	SEMTECH/UX
<b>Power:</b>	+3.3V single power supply
<b>Compliance:</b>	<ul style="list-style-type: none"> <li>• SFP MSA,</li> <li>• SFF-8472,</li> <li>• RoHS,</li> <li>• CE,</li> <li>• Class 1 FDA and IEC60825-1 Laser Safety Compliant</li> </ul>

## Compatibility

EDGE Optical transceivers can be provided with custom-encoded firmware, in order to provide compatibility with more than 50 vendor brands in data and telecom communications industry:

**MS** - General MSA  
**AD** - ADVA  
**AL** - Alcatel-Lucent  
**AR** - Arista  
**AV** - Avaya  
**BR** - Brocade  
**CN** - Ciena  
**CI** - Cisco  
**DL** - Dell & Force10  
**DK** - D-Link  
**EM** - EMC2  
**ET** - Enterasys

**ER** - Ericsson  
**EX** - Extreme Networks  
**F5** - F5 Networks  
**FO** - Fortinet  
**FU** - Fujitsu  
**H3** - H3C  
**HI** - Hirschmann  
**HP\*** - HP Networking  
**HS\*** - HP Storage  
**HU** - Huawei  
**IB** - IBM  
**IF** - Infinera

**IN** - Intel  
**JU** - Juniper Networks  
**LI** - Linksys  
**ML** - Mellanox  
**ME** - Meraki (Cisco)  
**MT** - MikroTik  
**MO** - Moxa  
**MR** - MRV  
**NG** - Netgear  
**NS** - NSN  
**PA** - Palo Alto Network  
**QL** - Qlogic

**RD** - RAD  
**RU** - Ruijie Networks  
**SM** - Supermicro  
**SY** - Synology  
**TC** - Telco Systems  
**TP** - TP-LINK  
**TN** - Trendnet  
**WG** - WatchGuard  
**ZT** - ZTE  
**XX** - Other

\* - Please note HP compatible module prices can be higher than prices indicated in this material due to special requirements in coding. If you require HP compatibility, for exact pricing please contact our sales team: [sales@edgeoptic.com](mailto:sales@edgeoptic.com)

## Product Quality

We focus on strict product quality tests before each delivery, performing optical parameter tests, connector cleanliness tests and firmware verification tests to ensure our delivered products fully meet the promised product technical specification and compatibility requirements.

EDGE Optical transceivers are CE, ROHS certified and have passed Telecordia reliability tests.

## Warranty

EDGE Optic's provides a limited **warranty for sixty (60) months** from Purchaser's receipt of the Equipment represented in this data sheet against defective design or workmanship.