

Key Highlights:

- **Type:** SFP28
- **Tx Wavelength:** 1270 nm - 1370 nm; 1470nm - 1610nm
- **Rx Wavelength:** G.694.2 CWDM Grid (1270-1610nm)
- **Media Type:** Single- Mode Fiber
- **Fiber Type:** Single-Mode Fiber (SMF)
- **Optical Budget:** 30 dB
- **Max. Distance:** 120 km
- **Data Rate:** 100-2.67Gbps
- **Temperature:** Standard 0°-70°C



Optical Transceiver : CWDM-2.67G-SFP-120-XX

Product Description:

CWDM-2.67G-SFP-120-XX is Multi-Vendor MSA Compatible SFP (Small Form factor Pluggable) Transceiver, operating over Double Fiber CWDM Single-Mode Fiber (SMF) optical cable. It has minimum guaranteed optical budget of 30 dB, with in most cases is enough to reach about 120 km distance. However, distance is just indicative parameter calculated for comfort of identification. Eventually we calculate distance taking in account minimal optical budget and average attenuation of optical cabling in industry. This transceiver use top quality DFB Laser transmitter with operating at nominal wavelength Ch. 27 – Ch. 61 (1270nm – 1610nm) APD Photodiode receiver. It support DDM/DOM optical diagnostics, with provide diagnostic information about the present operating conditions. CWDM-2.67G-SFP-120-XX operates in Standard 0°-70°C temperature range and has Double LC interface. SFP support 100-2.67Gbps data rate and such applications as STM-16 (2.488 Gbps)|STM-4 (622Mbps)|STM-1 (155Mbps)|100M Ethernet (100Mbps)|Gigabit Ethernet (1.25 Gbps)|1G Fiber Channel (1.0625 Gbps)|2G Fiber Channel (2.125 Gbps)|OTU1 (2.66Gbps)|ODU0 (1.244Gbps)|ODU1 (2.498Gbps)|CPRI option 3 (2.458 Gbps)|CPRI option 2 (1228.8 Mbps)|CPRI option 1 (614.4 Mbps)|OBSAI RP3 x 2 (1.536 Gbps)|OBSAI RP3 x 1 (768 Mbps). CWDM-2.67G-SFP-120-XX SFP Double Fiber CWDM optical transceiver is multi-purpose module used in number of different places of today's networking.



Consequently, most popular applications are SDH/SONET Links of Backbone, LTE 4G RRU and BBU Interconnections in C-RAN Fronthaul, Different Ethernet and Fiber Channel SAN Links in Enterprise Networks and other optical links.

Transceiver is CE/RoHS certified and it is Compliant with product safety standards. CWDM-2.67G-SFP-120-XX SFP Transceiver is fully compliant to SFP Multi Source Agreement INF-8074i. Consequently, it means that module is compatible with 80% of networking equipment, where is not implemented a special algorithm for protection against third party modules. However – we can provide SFP transceiver with custom-encoded firmware in order to make it work almost in any equipment. Therefore, we will be glad to know what your requirement is. Because our focus is providing top quality service, we are performing serious quality checks before delivery of our products. As a result, we do optical parameter measurements, connector cleanliness tests and SFP transceiver EEPROM memory data validation tests.

Product Specification:

General parameter	Value
Media Type:	Single-Mode Fiber (SMF)
Connectors:	Double LC
TX Wavelength:	Ch. 27 - Ch. 61 (1270nm - 1610nm)
RX Wavelength:	G.694.2 CWDM Grid (1270nm - 1610nm)
Minimum Optical Budget:	30 dB
Maximum Distance:	120km
Supported Data Rate:	100-2.67Gbps
Supported Applications:	Gigabit Ethernet (1.25 Gbps), 100M Ethernet (100Mbps), 2G Fiber Channel (2.125 Gbps), 1G Fiber Channel (1.0625 Gbps), STM-1 (155Mbps), STM-4 (622Mbps), STM-16 (2.488 Gbps), ODU0 (1.244Gbps), ODU1 (2.498Gbps), OTU1 (2.66Gbps), CPRI option 1 (614.4 Mbps), CPRI option 2 (1228.8 Mbps), CPRI option 3 (2.458 Gbps), OBSAI RP3 x 1 (768 Mbps), OBSAI RP3 x 2 (1.536 Gbps)
DDM/DOM:	Supported
Temperature Range:	Industrial -45°C – +85°C
Power Supply Voltage Typical:	+3.3V single power supply
Compliance:	CE, Class 1 FDA and IEC60825-1 Laser Safety Compliant, INF-8074i, RoHS, SFP MSA



Product Specification:

Transmitter Parameters:	Value
Transmitter Type:	EML Laser
Tx Wavelength Bandwidth:	20 nm (1270nm - 1610nm)
Minimum Transmitting Power:	0 dB
Maximum Transmitting Power:	5 dB

Receiver Parameters:	Value
Receiver Type:	PIN
Rx Wavelength Bandwidth:	G.694.2 grid: 1270nm - 1610nm
Receiver Sensitivity:	-30 dBm
Receiver Overload:	-7 dBm



Compatibility:

EDGE Optical transceivers can be provided with custom-encoded firmware, in order to provide compatibility with more than 100 vendor brands in data and telecom communications industry:

MS - General MSA**AD** - ADVA**AE** - Advantech**AL** - Alcatel (Nokia)**AT** - Allied Telesis**AR** - Arista**AS** - Arris**AV** - Avaya**BC** - Barracuda**BR** - Broadcom**QL** - Cavium (Qlogic)**CR** - Ceragon**CP** - Checkpoint**CH** - Chelsio**CN** - Ciena**CI** - Cisco**LI** - Cisco (Linksys)**CE** - Comnet**CO** - Coriant**DH** - Dahua**DC** - DCN**DL** - Dell & Force10**DK** - D-Link**DZ** - DZS(Dasan-Zhone)**EI** - ECI**EC** - EdgeCore**EW** - EdgeWare**EL** - Eltex**EM** - EMC2**EN** - Enterasys**ER** - Ericsson**EF** - EXFO**EX** - Extreme Networks**F5** - F5 Networks**FI** - Finisar**FO** - Fortinet**FU** - Fujitsu**H3** - H3C**HI** - Hirschmann**HU** - Huawei**IB** - IBM**IF** - Infinera**IN** - Intel**IX** - Ixia**JU** - Juniper Networks**KM** - KeyMile**KY** - KyLand**LN** - Lenovo**ML** - Mellanox**ME** - Meraki (Cisco)**MT** - MikroTik**MO** - Moxa**MR** - MRV**NC** - NEC**NG** - Netgear**NK** - Nokia**NT** - Nortel**NS** - NSN**OR** - Oracle**PA** - Palo Alto Network**PL** - Planet**QC** - QCT(Quanta)**QN** - QNAP**RD** - RAD**RW** - RadWare**RC** - Raisecom**RK** - Ruckus**RU** - Ruijie Networks**SG** - Samsung**SV** - Sandvine**SC** - Silicom**SF** - SolarFlare**SW** - Sonicwall**SM** - Supermicro**SY** - Synology**TC** - Telco Systems**TP** - TP-LINK**TN** - Trendnet**UN** - Ubiquiti Networks**VX** - VeEx**WG** - WatchGuard**WS** - Waystream**WT** - Westermo**ZT** - ZTE**ZX** - Zyxel**HP** - HP**AG** - Avago**OC** - Oclaro**EU** - Emulex**TM** - Transmode**AU** - HP Aruba**XX** - Other

Warranty:

EDGE Optic's provides a limited warranty for **sixty (60)** months from Purchaser's receipt of the Equipment represented in this data sheet against defective design or workmanship.

Ordering Information:

Part Number	Data Rate	Applications	Temperature Range	Available DWDM Channels
CWDM-2.67G-SFP-120-XX*	100-2.67Gbps	Up to 120 km	0°-70°C	27 to 61 ITU-T 100Ghz C-Band 1563.86nm to 1528.77nm

*XX represents the chosen channel, thus Ch.27 would be CWDM-2.67G-SFP-120-27 (1270nm)

