



## PRODUCT DATA SHEET

# Optical Transceiver: DWDM-10G-XENPAK-80-20

### Description:

DWDM-10G-XENPAK-80-20 is multi-vendor compatible XENPAK Transceiver module, operating over double fiber single-mode optical cable with maximum distance 80km. DWDM-10G-XENPAK-80-20 uses Ch. 20 (1561.42 nm) transmitting DFB laser and APD receiver supporting all ITU-T C-Band 100GHz Channel Spacing DWDM grid (Ch.17 – Ch.61) and supports 10.3125 Gbps Ethernet.

DWDM-10G-XENPAK-80-20 Transceiver is fully compliant to XENPAK MSA Rev.3 and it can be provided with custom-encoded firmware, in order to provide compatibility of most equipment vendors platforms in data communications industry.

### Key Highlights:

- **Type:** XENPAK
- **Tx/Rx Wavelength:** Ch 20 (1561.42 nm)/ ITU-T DWDM Grid 100 GHz C-Band
- **Media Type:** Single-Mode Fiber
- **Optical Budget:** 23dB
- **Max. Distance:** 80 km
- **Data Rate:** 10.3125Gbps
- **Temperature:** Standard 0°-70°C

# TECHNICAL SPECIFICATION

| Parameter                     | Value                                                                                                                                     |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Product Type:                 | DWDM-10G-XENPAK-80-20                                                                                                                     |
| Media Type:                   | Single-Mode Fiber                                                                                                                         |
| TX Wavelength:                | Ch 20 (1561.42 nm)                                                                                                                        |
| RX Wavelength:                | ITU-T 100GHz C-Band (Ch.17-Ch.61)                                                                                                         |
| Minimum Optical Budget:       | 23 dB                                                                                                                                     |
| Maximum Distance:             | 80 km                                                                                                                                     |
| Supported Data Rate:          | 10.3125Gbps                                                                                                                               |
| Supported Applications:       | 10G Eth (10.3125Gbps)                                                                                                                     |
| DDM/DOM:                      | Supported                                                                                                                                 |
| Temperature Range:            | Standard 0°-70°C                                                                                                                          |
| Connectors:                   | Double LC                                                                                                                                 |
| Tx Wavelength Bandwidth:      | 100GHz (0.8nm)                                                                                                                            |
| Rx Wavelength Bandwidth:      | 1260 - 1620 nm                                                                                                                            |
| Transmitting Power (Min/Max): | 0 / 4 dB                                                                                                                                  |
| Receiver Sensitivity:         | -23 dB                                                                                                                                    |
| Receiver Overload:            | -7 dB                                                                                                                                     |
| Dispersion:                   | 1600 ps/nm                                                                                                                                |
| Laser:                        | DFB                                                                                                                                       |
| Receiver Type:                | APD                                                                                                                                       |
| Chip:                         | SEMTECH/MAXIM/MINDSPEED                                                                                                                   |
| Power:                        | +3.3V single power supply                                                                                                                 |
| Compliance:                   | <ul style="list-style-type: none"><li>• XENPAK MSA Rev.3,</li><li>• CE, Class 1 FDA</li><li>• IEC60825-1 Laser Safety Compliant</li></ul> |

## Compatibility

EDGE Optical transceivers can be provided with custom-encoded firmware, in order to provide compatibility with more than 50 vendor brands in data and telecom communications industry:

**MS** - General MSA  
**AD** - ADVA  
**AL** - Alcatel-Lucent  
**AR** - Arista  
**AV** - Avaya  
**BR** - Brocade  
**CN** - Ciena  
**CI** - Cisco  
**DL** - Dell & Force10  
**DK** - D-Link  
**EM** - EMC2  
**ET** - Enterasys

**ER** - Ericsson  
**EX** - Extreme Networks  
**F5** - F5 Networks  
**FO** - Fortinet  
**FU** - Fujitsu  
**H3** - H3C  
**HI** - Hirschmann  
**HP\*** - HP Networking  
**HS\*** - HP Storage  
**HU** - Huawei  
**IB** - IBM  
**IF** - Infinera

**IN** - Intel  
**JU** - Juniper Networks  
**LI** - Linksys  
**ML** - Mellanox  
**ME** - Meraki (Cisco)  
**MT** - MikroTik  
**MO** - Moxa  
**MR** - MRV  
**NG** - Netgear  
**NS** - NSN  
**PA** - Palo Alto Network  
**QL** - Qlogic

**RD** - RAD  
**RU** - Ruijie Networks  
**SM** - Supermicro  
**SY** - Synology  
**TC** - Telco Systems  
**TP** - TP-LINK  
**TN** - Trendnet  
**WG** - WatchGuard  
**ZT** - ZTE  
**XX** - Other

\* - Please note HP compatible module prices can be higher than prices indicated in this material due to special requirements in coding. If you require HP compatibility, for exact pricing please contact our sales team: [sales@edgeoptic.com](mailto:sales@edgeoptic.com)

## Product Quality

We focus on strict product quality tests before each delivery, performing optical parameter tests, connector cleanliness tests and firmware verification tests to ensure our delivered products fully meet the promised product technical specification and compatibility requirements.

EDGE Optical transceivers are CE, ROHS certified and have passed Telecordia reliability tests.

## Warranty

EDGE Optic's provides a limited **warranty for sixty (60) months** from Purchaser's receipt of the Equipment represented in this data sheet against defective design or workmanship.