



## PRODUCT DATA SHEET

# Optical Transceiver: DWDM-10G-XFP-80-TUN-F

### Description:

DWDM-10G-XFP-80-TUN-F is multi-vendor compatible tunable XFP module, operating over double fiber single-mode optical cable with maximum distance 80 km. DWDM-10G-XFP-80-TUN-F support ITU 50GHz Grid: C-Band (Ch17-61) and uses transmitting monolithic MZM Tunable TOSA laser and APD receiver supporting all ITU-T G.694.2 grid 1270-1610nm. Module supports 8.5-11.32Gbps data rates.

DWDM-10G-XFP-80-TUN-F XFP Transceiver is fully compliant to XFP MSA, RoHS-6 and it can be provided with custom-encoded firmware, in order to provide compatibility of most equipment vendor's platforms in data communications industry.

### Key Highlights:

- **Type:** XFP
- **Tx/Rx Wavelength:** ITU 50GHz Grid: C-Band (Ch17-61)/ 1270-1610nm
- **Media Type:** Single-Mode Fiber
- **Optical Budget:** 22 dB
- **Max. Distance:** 80 km
- **Data Rate:** 8.5-11.32Gbps
- **Temperature:** Standard 0°-70°C

# TECHNICAL SPECIFICATION

Parameter	Value
<b>Product Type:</b>	DWDM-10G-XFP-80-TUN-F
<b>Media Type:</b>	Single-Mode Fiber
<b>TX Wavelength:</b>	ITU 50Ghz Grid: C-Band (Ch17-61)
<b>RX Wavelength:</b>	1270-1610 nm
<b>Minimum Optical Budget:</b>	22 dB
<b>Maximum Distance:</b>	80 km
<b>Supported Data Rate:</b>	8.5-11.32Gbps
<b>Supported Applications:</b>	<ul style="list-style-type: none"> <li>• 10G Eth (10.31Gbps)</li> <li>• 1G Eth (1.25Gbps)</li> <li>• STM-64 (9.95Gbps)</li> <li>• STM-16 (2.488 Gbps)</li> <li>• OTU1 (2.66Gbps)</li> <li>• OTU2 (10.70Gbps)</li> <li>• OTU1e (11.049Gbps)</li> <li>• OTU2e (11.095Gbps)</li> <li>• OTU1f (11.27Gbps)</li> <li>• OTU2f (11.32Gbps)</li> <li>• ODU0 (1.244Gbps)</li> <li>• ODU1 (2.498Gbps)</li> <li>• ODU2 (10.037Gbps)</li> <li>• ODU2e (10.399Gbps)</li> <li>• 10G FC (10.52 Gbps)</li> <li>• 8.5G FC (8.5 Gbps)</li> <li>• 4G FC (4.25 Gbps)</li> <li>• 2G FC (2.125 Gbps)</li> <li>• 1G FC (1.0625 Gbps)</li> </ul>
<b>DDM/DOM:</b>	Supported
<b>Temperature Range:</b>	Standard 0°-70°C
<b>Connectors:</b>	Double LC
<b>Tx Wavelength Bandwidth:</b>	ITU 50Ghz Grid: C-Band (Ch17-61)
<b>Rx Wavelength Bandwidth:</b>	G.694.2 grid: 1270-1610 nm
<b>Transmitting Power (Min/Max):</b>	-1/3 dBm
<b>Receiver Sensitivity:</b>	-22 dBm
<b>Receiver Overload:</b>	-7 dB -8 dBm

Parameter	Value
<b>Dispersion:</b>	1600 ps/nm
<b>Laser:</b>	Monolithic MZM Tunable TOSA
<b>Receiver Type:</b>	APD
<b>Power:</b>	+3.3V single power supply
<b>Compliance:</b>	XFP MSA, RoHS, CE, Class 1 FDA and IEC60825-1 Laser Safety Compliant

## Compatibility

EDGE Optical transceivers can be provided with custom-encoded firmware, in order to provide compatibility with more than 50 vendor brands in data and telecom communications industry:

**MS** - General MSA  
**AD** - ADVA  
**AL** - Alcatel-Lucent  
**AR** - Arista  
**AV** - Avaya  
**BR** - Brocade  
**CN** - Ciena  
**CI** - Cisco  
**DL** - Dell & Force10  
**DK** - D-Link  
**EM** - EMC2  
**ET** - Enterasys

**ER** - Ericsson  
**EX** - Extreme Networks  
**F5** - F5 Networks  
**FO** - Fortinet  
**FU** - Fujitsu  
**H3** - H3C  
**HI** - Hirschmann  
**HP\*** - HP Networking  
**HS\*** - HP Storage  
**HU** - Huawei  
**IB** - IBM  
**IF** - Infinera

**IN** - Intel  
**JU** - Juniper Networks  
**LI** - Linksys  
**ML** - Mellanox  
**ME** - Meraki (Cisco)  
**MT** - MikroTik  
**MO** - Moxa  
**MR** - MRV  
**NG** - Netgear  
**NS** - NSN  
**PA** - Palo Alto Network  
**QL** - Qlogic

**RD** - RAD  
**RU** - Ruijie Networks  
**SM** - Supermicro  
**SY** - Synology  
**TC** - Telco Systems  
**TP** - TP-LINK  
**TN** - Trendnet  
**WG** - WatchGuard  
**ZT** - ZTE  
**XX** - Other

\* - Please note HP compatible module prices can be higher than prices indicated in this material due to special requirements in coding. If you require HP compatibility, for exact pricing please contact our sales team: [sales@edgeoptic.com](mailto:sales@edgeoptic.com)

## Product Quality

We focus on strict product quality tests before each delivery, performing optical parameter tests, connector cleanliness tests and firmware verification tests to ensure our delivered products fully meet the promised product technical specification and compatibility requirements.

EDGE Optical transceivers are CE, ROHS certified and have passed Telecordia reliability tests.

## Warranty

EDGE Optic's provides a limited **warranty for sixty (60) months** from Purchaser's receipt of the Equipment represented in this data sheet against defective design or workmanship.